

LED MR16 SPOT LAMPS 1 Watt and 4 Watt and 4.3 Watt GU5.3, GU10, and E26 Base



(1X1W) - RMS-PT161001
(1X3W) - RMS-PT161003



(1X1W) - RMS-PT101001
(1X3W) - RMS-PT101003



(1X1W) - RMS-PT261001
(1X3W) - RMS-PT261003



(3X1W) - RMS-PT163003



(3X1W) - RMS-PT104003



(3X1W) - RMS-PT264003

Raptor Lighting® Part Number	GU5.3 Base	GU10 Base	E26 Base
	(1X1W) - RMS-PT161001 (1X3W) - RMS-PT161003 (3X1W) - RMS-PT163003	(1X1W) - RMS-PT101001 (1X3W) - RMS-PT101003 (3X1W) - RMS-PT104003	(1X1W) - RMS-PT261001 (1X3W) - RMS-PT261003 (3X1W) - RMS-PT264003
Features	Non-Dimmable		
Input Voltage	AC/DC 12 Volts	AC 100~240 Volts	
Frequency Range	50~60 Hz		
Number of LEDs	1 Pcs x 1W 1 Pcs x 3W 3 Pcs x 1W		
LED Manufacturer	Epistar		
Total Power Consumption	1.6 Watt (1X1W) 4 Watt (1X3W) 4.3 Watt (3X1W)		
Lumens	60~73~80 Lumens (1X1W) 95~110~120 Lumens (1X3W) 150~180~200 Lumens (3X1W)		
Beam Angle	1X1W = 26° 1X3W = 26° 3X1W = 15°		
CRI	>70		
Color Temperature	3000K (+/-300K)	5500K (+/-500K)	9000K (+/-1000K)
LED Life	50,000+ Hours		
Material	Aluminum		
Lamp Base	GU5.3	GU10	E26
Outline Dimension (inches)	2" (D) x 1.8" (L)	2" (D) x 2.2" (L)	2" (D) x 2.2" (L)
Case Quantity	240		
Listings and Certifications	UL Listed		