

LED T8 LINEAR LAMP

UL Listed and LM-79 Approved



Raptor Part Number	RMS-TB2606-35BC1B	RMS-TB2609-35BC1C	RMS-TB2612-35BC1E
	RMS-TB2606-41BC1B	RMS-TB2609-41BC1C	RMS-TB2612-41BC1E
	RMS-TB2606-51BC1B	RMS-TB2609-51BC1C	RMS-TB2612-51BC1E
	RMS-TB2606-65BC1B	RMS-TB2609-65BC1C	RMS-TB2612-65BC1E
	RMS-TB2606-35BF1B	RMS-TB2609-35BF1C	RMS-TB2612-35BF1E
	RMS-TB2606-41BF1B	RMS-TB2609-41BF1C	RMS-TB2612-41BF1E
	RMS-TB2606-51BF1B	RMS-TB2609-51BF1C	RMS-TB2612-51BF1E
	RMS-TB2606-65BF1B	RMS-TB2609-65BF1C	RMS-TB2612-65BF1E
Features	Non-Dimmable		
Additional Features	Clear (-C)		Frosted (-F)
Input Voltage	AC 85~277 Volts		
Power Factor	> 0.9		
Frequency Range	50~60 Hz		
Number of LEDs	144 pieces	168 pieces	288 pieces
LED Manufacturer and Type	Epistar ~ SMD 3528 LED		
Total Power Consumption	8 Watt	13 Watt	18 Watt
Lumens	704~752 Lm	1144~1222 Lm	1584~1692 Lm
Beam Angle	See Table Below For Specific Lumens Per Color Temperature		
Beam Angle	120°		
CRI	65~80		
Color Temperature	3200K	4100K	5100K 6500K
Operation Temperature	-22°F to 122°F		
LED Life	50,000+ Hours		
Outline Dimension (inches)	24" (length)	36" (length)	48" (length)
Direct Replacement – T8 Fluorescent	17 Watt	25 Watt	32 Watt
Case Quantity	50	25	25
Listings and Certifications	UL Listed and LM-79 Approved		

Wattage	3200K	4100K	5100K	6500K
	Lumens Clear Cover Lumens Frosted Cover	Lumens Clear Cover Lumens Frosted Cover	Lumens Clear Cover Lumens Frosted Cover	Lumens Clear Cover Lumens Frosted Cover
8W	736 Lumens 647 Lumens	752 Lumens 661 Lumens	720 Lumens 634 Lumens	704 Lumens 620 Lumens
13W	1196 Lumens 1053 Lumens	1222 Lumens 1079 Lumens	1170 Lumens 1027 Lumens	1144 Lumens 1014 Lumens
18W	1656 Lumens 1458 Lumens	1692 Lumens 1494 Lumens	1620 Lumens 1422 Lumens	1584 Lumens 1404 Lumens